

INTERIOR & EXTERIOR APPLICATION

For ramps, tiles and cement topping only.

Not recommended for installation in rebated grooves in marble, granite, stone, terrazzo or timber treads where metal supported products or Titazel ST Trowelable Resin Safety Tread should be considered.



Mall bars inserted in treads.



Various mall bar sizes and colours.

PRODUCT GUIDE – MALL BARS & STUDS

Optional Supagrit infill colours available at extra cost.

Mall Bars	Width	Depth
US 12	12	10
US 15	15	10
US 20	20	10
US 25	25	10
US 40	40	10
US 50	50	10

All measurements in millimetres



*lumo
*Lumo Luminescent glow-in-the-dark infill.
Colours are indicative only. Batch colours may vary and amber.

Standard colour is sparkling black.

Other colours available are: brown, teak, silver grey, cactus green, blue, blue grey, terracotta, lumo luminescent, off white, safety yellow, buff and teal (batch colours may vary and amber).

Standard length is 1000mm, longer lengths are available on special order.

Service factors must be taken into consideration when selecting tread and mall bar width, duty and installation configuration.



Abrasive Studs

15mm, 25mm, 50mm, 75mm and 100mm. Installed in drilled holes using Titazel Thixotropic Resin Adhesive. Any timber to accept studs should be presealed.



Titazel™ ST Trowelable Resin Safety Tread for trowelling in groove applications. See information page 30 for further details.



US22 Unsupported mall bar (custom made) installed with Titazel Thixotropic Adhesive in front of suitably prepared steel grating. Titazel ST Trowelable Resin Safety Tread can also be used for this application.