

## INTERIOR & EXTERIOR APPLICATION – COMMERCIAL & INDUSTRIAL USE

**Asbra™ SAF-T™ Abrasive Safety Slip Resistant Surface Coating** is a 2-part heavy duty epoxy liquid abrasive surface coating which has been researched and developed for simple application. It is a cost effective safety coating that can be applied in minutes over concrete, metal or timber after suitable preparation of the surface. It is safe, tough and durable, can be used in internal and external applications. It is odourless after cure and is suitable for vehicular traffic.

Cure time 12/24 hours at 25°C. Full cure 7 days.

### Coverage

Depending on surface texture. When applied on flat, smooth, clean surface Standard Pack SAF-T™ 5 covers approximately 5 metres<sup>2</sup>.

Bulk Pack SAF-T™ 25 covers approximately 25 metres<sup>2</sup>.

### Application

The product can be applied using a hard roller (preferred method), brush or trowel. The application method will have an effect on the finish.

### Maintenance

Wash regularly with light duty solution of Latham Gold-Chem Neutral Ph Chemical Cleaner.

Available in 1, 5 and 35Kg packs.

### Colours

Standard SAF-T™ colour is safety yellow. SAF-T™ is available in a range of 5 colours to accent or harmonise in most applications.



**A liquid abrasive surface coating which has been researched and developed for simple application**

### SAF-T COLOUR GUIDE

Standard colour is safety yellow. SAF-T is available in a range of 5 colours to accent or harmonise in most applications.



Colours may vary and amber.