Latham Roof-Line Series Aluminium Expansion Joint Cover **FWL**



Flashing and caulking by others Wall member factory drilled to accept countersunk 110mm head 6.5mm fixings Splice cover 36mm Side member factory drilled with 10mm holes at approximately С 475mm centres

Illustrated: FWL-50





Aluminium Code	A	В	С	Movement	Total Available Movement	Overall Depth
FWL-25	25	75	70	+20/-15mm	35mm	110mm
FWL-50	50	108	70	+25/-40mm	65mm	110mm
FWL-75	75	132	70	+25/-65mm	90mm	110mm
FWL-100	100	158	70	+25/-90mm	115mm	110mm
FWL-150	150	208	70	+25/-140mm	165mm	110mm

FEATURES

- Shallow aluminium roof-to-parapet expansion joint cover.
- Designed for installation on flat concrete or timber hobs, plinths or concrete roofs.
- Comes with standard water/wind barrier and top seal gaskets for the centre plate screw.
- Supplied with 1 splice plate per full length for installation over the junction between 2 plates.

MATERIALS

- Aluminium 6063-T5 mill finish alloy.
- Supplied in 3050mm lengths.

FIXINGS

 Side member pre-drilled at ~475mm centres for 10mm fasteners.

- Wall member pre-drilled at ~475mm centres to accept countersunk head 6.5mm fixings.
- End Closures, Transition Splices, Corners and Tees should be considered for roof joints. (Contact a Latham representative for more information)

FURTHER TECHNICAL SPECIFICATIONS

- Website Link PDF and DWG Details
- <u>Product Information</u>
- Joint Specifications
- Fire Rated Systems
- Full Product Catalogue
- Architectural Specifications
- Warranty











e sales@latham-australia.com

p +612 9879 7888

