ASMPL PAVA Series

All dimensions are in millimetres.

Flexible Mechanical Expansion Joint Cover

LATHAM AUSTRALIA PTY LTD

14 TENNYSON ROAD GLADESVILLE 2111 AUSTRALIA Phone: 61 2 9879 7888 Fax: 61 2 9879 7666 Web: www.latham-australia.com

Design subject to change without notice.



COPYRIGHT © 2025

Illustrated: ASMPL PAVA **Not to Scale** All dimensions are to be verified before construction Verified By..... Date..... Wall member STONE/TILE INLAY factory drilled Н **←**E→ to accept SUITABLE FILL 6.5mm countersunk head fixings Pack with **BFG Water Gutter** Side members high strength factory drilled with non-shrink grout 10mm holes at approximately 475mm centres Contact your Latham Representative to discuss the application and specification of this system. **Total Available** Cover **Aluminium Code** Movement Serrated Flange Movement **Thickness** Suitable for joint widths up to 100mm. The minimum overall recess required to accommodate this system regardless of the joint width is 315mm. Recessing of the stone as detailed above is not 4mm ASMPL-25 +/-22mm 44mm necessary. The product can simply sit on the surface of the stone as per photo. ASMPL-50 +/-22mm 44mm 4mm Exterior/Interior applications. ASMPL-75 75 175 125 50 25 22 35 30 93 44mm +/-22mm 4mm ASMPL-100 100 175 125 50 25 22 35 30 93 +/-22mm 44mm 4mm All mechanical expansion joint fixings by others.