BSMPL PAVA Series 14 TENNYSON ROAD GLADESVILLE 2111 AUSTRALIA Phone: 61 2 9879 7888 Fax: 61 2 9879 7666 Flexible Mechanical Expansion Joint Cover Web: www.latham-australia.com Illustrated: BSMPL PAVA Not to Scale All dimensions are to be verified before construction В Verified By..... Date..... Π STONE/TILE INLAY E Wall member GΗ factory drilled SUITABLE FILL to accept countersunk head 6.5mm fixings Side members BFG Water Gutter factory drilled with [⊥] 10mm holes at approximately 400mm centres

Contact your Latham Representative to discuss the application and specification of this system.

Brass Code	A	в	с	D	E	F	G	н	I	Movement	Total Available Movement	Cover Thickness
BSMPL-25	25	231	200	31	12	22	41	37	93	+/-12mm	24mm	4mm
BSMPL-50	50	231	200	31	12	22	41	37	93	+/-12mm	24mm	4mm
BSMPL-75	75	231	200	31	12	22	41	37	93	+/-12mm	24mm	4mm
BSMPL-100	100	231	200	31	12	22	41	37	93	+/-12mm	24mm	4mm
All dimensions are in millimetres.												

Suitable for joint widths up to 100mm. The minimum overall recess required to accommodate this system regardless of the joint width is 315mm. Recessing of the stone as detailed above is not necessary. The product can simply sit on the surface of the stone as per photo.

Exterior/Interior applications.

All mechanical expansion joint fixings by others.

ATHAM AUSTRALIA PTY LTD

Design subject to change without notice.

COPYRIGHT © 2025