NBBL Brass Flat-Line Series - No Bump

Flexible Expansion Joint Cover

LATHAM AUSTRALIA PTY LTD

14 TENNYSON ROAD GLADESVILLE 2111 AUSTRALIA Phone: 61 2 9879 7888 Fax: 61 2 9879 7666 Web: www.latham-australia.com



Illustrated: NBBL-55 Scale: Approx. Full Size
All dimensions are to be verified before construction

All anchors are supplied welded to the side members at approximately 475mm centres. BM-16 anchors are supplied factory drilled with 10mm holes at approximately 475mm centres

B C 35mm Wall member

BM-16 Anchor

BS-6 Cast-In
Anchor (optional)

factory drilled to accept countersunk head 6.5mm fixings

OPTIONAL HEIGHTS AVAILABLE

Standard: 25mm

Optional: 32mm, 54mm, 64mm, 79mm, 89mm, 104mm, 114mm, 139mm, 164mm

Solid Brass Co	le A	В	С	D	Е	F	Movement	Total Available Movement	Overall Depth	Cover Plate Thickness
NBBL-5	55	87	78	8	3	66	+22/-3mm	25mm	25mm	3mm
NBBL-8	80	111	103	8	3	66	+22/-3mm	25mm	25mm	3mm
NBBL-10	5 105	171	163	8	4	75	+47/-3mm	50mm	25mm	3mm
NBBL-13	130	196	188	8	4	75	+47/-3mm	50mm	25mm	5mm

Larger joint widths available on request. All dimensions are in millimetres.

Exterior/Interior use.

The Latham No-Bump Series of joints have been specially designed by Latham Australia Pty. Ltd. for use in Hospitals and other applications where no change in floor surface level can be tolerated. The inverted Brass Cover Plate alleviates any bump. NBBL joints are available in all standard joint widths, as CAB and joints, please refer to Latham Technical Manual 43.

All mechanical expansion joint fixings by others.

Design subject to change without notice.

COPYRIGHT © 2009

LATH3513