## SAA (SSSM) Ultimate Series - Deep

Flexible Mechanical Expansion Joint Cover

## LATHAM AUSTRALIA PTY LTD

14 TENNYSON ROAD GLADESVILLE 2111 AUSTRALIA Phone: 61 2 9879 7888 Fax: 61 2 9879 7666 Web: www.latham-australia.com



14mm

65mm

(varies)

Exterior/Interior use.

All mechanical expansion joint fixings by others.

Aluminium embedded members on continuous treated steel angle supports with specified cover plate.

The centering bar consists of two full nylon spheres fastened at opposite ends of a flat spring steel bar. The bar is positioned diagonally across the joint opening with the spheres inside the extruded cylindrical tracks. This unique concept allows for increased rotational movements and maintains constant spring tension at the centre of the cover plate. This greatly reduces the stresses on the embedded anchor sections and the surrounding concrete slabs.

Design subject to change without notice.

Continuous treated steel angle supports factory drilled with 10mm holes at approximately 475mm centres

▲ Specify required depth i.e. SAA-25 (SSSM 79) as drawn.

Available depths: 79mm, 89mm, 104mm, 114mm, 139mm & 164mm.

"F" distance subject to required depth.

 Aluminium Code ribbed deck
 A
 B
 C
 D
 E
 F
 Movement Movement
 Total Available Movement
 Overall Depth Movement
 Cover Plate Thickness

 SAA-25 (SSSM ▲)
 25
 87
 50
 18
 13
 ◆ +20/-15mm
 35mm
 Specify
 3mm

 SAA-50 (SSSM ▲)
 50
 113
 75
 18
 13
 ◆ +20/-25mm
 45mm
 Specify
 3mm

All dimensions are in millimetres.

Optional BFG Water Gutter

COPYRIGHT © 2009

LATH3513