GOOD DESIGN AWARD® WINNER

AUSTRALIAN MADE AND OWNED

Features

Multidirectional 4-way Movement

Indoor Use

LATHAM 5 Year GENUINE WARRANTY

Application

- Floor, Floor-to-Wall, Wall & Ceiling expansion joint covers.
- Internal light duty, moderate traffic applications only, where limited movement is expected.
- The 50-Series joint covers allow a maximum of ±5mm of horizontal movement.
- The 50-Series offers the opportunity to use the most similar joint cover in the wall and ceiling to the floor. This is particularly effective when the construction joint forms a square box shape. See WR and WCR Series.

Materials

- Aluminium 6063-T5 mill finish alloy.
- Supplied in 4000mm lengths.
- Standard replaceable synthetic rubber inserts are grey. Beige or black can be supplied on request.

Fixings

- Side members factory drilled with 10mm holes at ~475mm centres.
- Wall members factory drilled to accept 8mm gauge screw and plug at ~475mm centres on request.

FOR FURTHER TECHNICAL SPECIFICATIONS VISIT WWW.LATHAM-AUSTRALIA.COM

INSERT COLOUR SELECTION

Grey Black Beige

50-FDR & 50-FDRW Aluminium Floor & Floor-to-Wall Expansion Joint Covers



TECHNICAL CHARACTERISTICS

Aluminium Code	A	B	C	D	E	F	Movement	Total Available Movement	Overall Depth
50-FDR	50	48	42	50	50	n/a	+/-5mm	10mm	50mm
50-FDRW	50	45	42	50	50	38	+/-5mm	10mm	88mm

50-FDR(30) & 50-FDRW(30) Aluminium Floor & Floor-to-Wall Expansion Joint Covers



TECHNICAL CHARACTERISTICS

Aluminium Code	A	B	C	D	E	F	Movement	Total Available Movement	Overall Depth
50-FDR (30)	50	48	42	50	30	n/a	+/-5mm	10mm	30mm
50-FDRW (30)	50	45	42	50	30	38	+/-5mm	10mm	68mm

50-FDR(20) & 50-FDRW(20) Aluminium Floor & Floor-to-Wall Expansion Joint Covers



TECHNICAL CHARACTERISTICS

Aluminium Code	A	B	C	D	E	F	Movement	Total Available Movement	Overall Depth
50-FDR (20)	50	48	42	50	20	n/a	+/-5mm	10mm	20mm
50-FDRW (20)	50	46	42	50	20	38	+/-5mm	10mm	59mm

+61 2 9879 7888
joints@latham-australia.com

Designs and specifications subject to change without notice.