



**GOOD
DESIGN
AWARD®
WINNER**



Features



Multidirectional
4-way Movement



Indoor Use



Application

- Floor, Floor-to-Wall, Wall & Ceiling expansion joint covers.
- Internal light duty, low traffic applications only, where limited movement is expected.
- The B70-Series joint covers allow a maximum of $\pm 10\text{mm}$ of horizontal movement.

Materials

- Aluminium 6063-T5 mill finish alloy.
- Supplied in 3600mm lengths.
- Standard replaceable synthetic rubber inserts are beige. Grey or black can be supplied on request.

Fixings

- Side members factory drilled with 10mm holes at $\sim 475\text{mm}$ centres.
- Brass anodised wall member factory drilled to accept 8mm gauge screw and plug at $\sim 475\text{mm}$ centres on request.

FOR FURTHER TECHNICAL
SPECIFICATIONS VISIT
WWW.LATHAM-AUSTRALIA.COM

INSERT COLOUR SELECTION



Grey




Black



Beige


B70-FDR & B70-FDRW Brass Clad Floor & Floor-to-Wall Expansion Joint Covers



TECHNICAL CHARACTERISTICS

Brass Clad Code	A	B	C	D	E	F	Movement	Total Available Movement	Overall Depth
B70-FDR	70	71	65	50	51	n/a	$\pm 10\text{mm}$	20mm	50mm
B70-FDRW	70	68	65	50	51	38	$\pm 10\text{mm}$	20mm	88mm


B70-FDR(30) & B70-FDRW(30) Brass Clad Floor & Floor-to-Wall Expansion Joint Covers



TECHNICAL CHARACTERISTICS

Brass Clad Code	A	B	C	D	E	F	Movement	Total Available Movement	Overall Depth
B70-FDR(30)	70	71	65	50	31	n/a	$\pm 10\text{mm}$	20mm	30mm
B70-FDRW(30)	70	68	65	50	31	38	$\pm 10\text{mm}$	20mm	68mm

B70-FDR(20) & B70-FDRW(20) Brass Clad Floor & Floor-to-Wall Expansion Joint Covers



TECHNICAL CHARACTERISTICS

Brass Clad Code	A	B	C	D	E	F	Movement	Total Available Movement	Overall Depth
B70-FDR(20)	70	71	65	50	21	n/a	$\pm 10\text{mm}$	20mm	20mm
B70-FDRW(20)	70	68	65	50	21	38	$\pm 10\text{mm}$	20mm	58mm