


SAA-25 (FASM 50) to SAA-50 (FASM 50) Aluminium Floor-to-Floor Expansion Joint Cover with Ribbed Deck



Features



Multidirectional
6-way Movement



Water Gutter
Available



Indoor Use



Outdoor Use



Anti-Tamper
Tie Bar Screws
Available



Slip Resistant
Sumo Grip (P4)
Coating Available



Fire Rateable

The SAA (FASM 50) Ultimate Series robust floor-to-floor expansion joint covers are designed to be fixed with floor finishes to 50mm deep, intended predominantly for pedestrian applications. These joints can be used in conjunction with many floor finishes such as concrete toppings, terrazzo, tile, pavers and stone. They would commonly be used in locations such as shopping centres, hotels, office foyers, schools, airports and other pedestrian traffic situations.

TECHNICAL CHARACTERISTICS

Illustrated: SAA-50 (FASM 50)


Aluminium Code Ribbed Deck	A	B	C	D	E	F	Movement	Total Available Movement	Overall Depth	Cover Plate Thickness
SAA-25 (FASM 50)	25	86	50	18	13	60	+20/-15mm	35mm	50mm	3mm
SAA-50 (FASM 50)	50	111	75	18	13	60	+20/-25mm	45mm	50mm	3mm

Materials

- Aluminium 6063-T5 mill finish alloy.
- Supplied in 3050mm lengths.
- Spring steel treated centring bar with nylon spherical balls at ~475mm centres.

Fixings

- Side members factory drilled with 10mm holes at ~475mm centres.



Wider joint widths available on request.

All dimensions in millimetres. All mechanical expansion joint fixings by others.

Further technical specifications and information – visit www.latham-australia.com

- PDF & DWG Details
- Architectural Specs
- Warranty Details
- Product Information
- Fire Rated Systems
- Working Video
- Joint Cover Specs
- Product Catalogue