


LATHAM NEOPRENE-X-PANSION LOC® STRIPS



3MM-LSZ 50x6 Zinc/Grey Loc Strip showing optional GW50/SSW50 Wire Anchors for maximum control.

Loc® Strips 6MM NEOPRENE INSERT WITH 3MM SIDE PLATES

The tables and information on these pages indicate some of the available 6mm Loc® Strip configurations with 3mm thick Brass and Zinc side plates. Illustrations show some of the colour combinations available for the neoprene inserts and the 3mm metal side plates.

Latham 6mm Neoprene-X-Pansion Loc® Strips, with 3mm side plates are generally used in interior applications where the expected thermal expansion of floor finish would be considered less than an external application. They are also suitable for external applications as well, however the bay sizes or distance between the strips will need to be reduced (see pages 4-6 for further set out and spacing details)).

Latham 6mm Neoprene-X-Pansion Loc® Strips with 3mm side plates are intended to be used in all hard flooring applications and are designed to be installed in conjunction with wet bedded flooring applications (see pages 52-53 for further installation details). Although the 3mm side plates are harder wearing than the standard 1mm brass and zinc side plates, correctly fixed Loc® Strips, installed flush with the surrounding floor finish should not be impacted by loads and traffic.


Latham 6mm Neoprene-X-Pansion Loc® Strips, with 3mm side plates are supplied in standard 1800mm lengths and should be installed so as to minimise the frequency of butt joints and short lengths. Also 3-way and 4-way butt joint intersections should be avoided (see page 54 for further details).

All Latham Neoprene-X-Pansion Loc® Strips are designed specifically for use with optional GW50/SSW50 Wire Anchors for maximum control. For further information and specification details, see page 55 or for full details visits our website www.latham-australia.com.

Latham Neoprene-X-Pansion Loc® Strips should be installed in all locations of stress concentration; at changes in direction; wherever localised movement is anticipated and around rigid and fixed large objects such as columns, stair and lift wells, light posts, across driveways, at access covers, across doorways and anywhere that may impede expansion and contraction of the floor finish.



6MM NEOPRENE INSERT – 3MM SIDE PLATES



WIRE ANCHORS
Optional galvanised GW50 or stainless steel SSW50 (external application) auxiliary wire anchors.

- 1. 3MM-LSZ 50X6 ZINC/GREY
- 2. 3MM-LSBL 40X6 BRASS/BUFF
- 3. 3MM-LSB 31X6 BRASS/BLACK

GENERAL PRODUCT INFORMATION

- Supplied in standard lengths of 1800mm.
- Loc® Strips are specifically designed for use with optional GW50/SSW50 Wire Anchors for maximum control.
- Product profile illustrations approximately 66% full size.

6MM WIDE NEOPRENE-X-PANSION LOC STRIPS WITH 3MM THICK SIDE PLATES PROFILE GUIDE			
Specify Neoprene Colour and Wire Anchors			
Brass (3mm thick side plates)	Zinc (3mm thick side plates)	Overall Product Depth	Accommodates Paving Maximum Thickness (with GW-50/SSW-50 wire anchors in place)
3MM-LSB-22 x 6	3MM-LSZ-22 x 6	22mm	8mm
3MM-LSB-31 x 6	3MM-LSZ-31 x 6	31mm	15mm
3MM-LSBL-40 x 6	3MM-LSZL-40 x 6	40mm Low Loop	30mm
3MM-LSB-50 x 6	3MM-LSZ-50 x 6	50mm	35mm
3MM-LSBL-50 x 6	3MM-LSZL-50 x 6	50mm Low Loop	40mm
3MM-LSB-65 x 6	3MM-LSZ-65 x 6	65mm	50mm
3MM-LSB-80 x 6	3MM-LSZ-80 x 6	80mm	65mm
3MM-LSB-90 x 6	3MM-LSZ-90 x 6	90mm	75mm
3MM-LSB-100 x 6	3MM-LSZ-100 x 6	100mm	85mm
3MM-LSB-115 x 6	3MM-LSZ-115 x 6	115mm	100mm
☛ Custom heights to accommodate custom floor finish thicknesses available on request.			
☛ Contact Latham Australia with your requirements.			



NEOPRENE INFILL COLOUR OPTIONS

BU Buff	GR Grey	BL Black
----------------	----------------	-----------------

METAL SIDE PLATE OPTIONS

BR Brass 3mm	ZN Zinc 3mm
---------------------	--------------------