



Interior and Exterior Application

For Ramps, Tiles and Cement Topping Only

Not recommended for installation in rebated grooves in marble, granite, stone, terrazzo or timber treads where metal supported products or Titazel ST Trowelable Resin Safety Tread should be considered.

Standard colour is sparkling black.

Other colours available are: brown, teak, silver grey, cactus green, blue, blue grey, terracotta, lumo luminescent, off white, safety yellow, buff and teal (batch colours may vary and amber). For colour range see page 66.

Standard length is 1000mm. Longer lengths are available on special order.



Mall Bars	Width	Depth
US 12	12mm	10mm
US 15	15mm	10mm
US 20	20mm	10mm
US 25	25mm	10mm
US 40	40mm	10mm
US 50	50mm	10mm

Service factors must be taken into consideration when selecting tread and mall bar width, duty and installation configuration.



Slip-Resistant Infill Colour Range

Optional Supagrit infill colours available at extra cost. Colours are indicative only.



sparkling black



brown



buff



terracotta



silver grey



off white



teak



cactus green



blue



blue grey



safety yellow



teal



\*lumo

\*Lumo-Luminescent glow-in-the-dark infill

Designs and specifications subject to change without notice.



## Interior and Exterior Application

### Aluminium Clad Abrasive Studs

Aluminium Clad Abrasive Studs are clad with approximately 2mm thick aluminium. They are 10mm deep and available in a range of colours for insertion into predrilled holes in timber, concrete or stone.

The systems have Latham Standard Slip Resistant Silicon Carbide Mineral Inserts for safety. Where these are being considered for installation on stairs as a slip resistant treatment. We suggest that the studs are installed no further apart than 50mm to ensure that the pedestrians foot is on a stud at all times.

The Aluminium Clad Abrasive Studs should be installed using Titazel Thixotropic adhesive.

Any timber to accept studs should be presealed. For colour range see page 66.

Clad Studs	Outside Diameter	Depth
AAS-15	15mm	10mm
AAS-25	25mm	10mm
AAS-50	50mm	10mm
AAS-75	75mm	10mm
AAS-100	100mm	10mm



Service factors must be taken into consideration when selecting tread and mall bar width, duty and installation configuration.

Further slip resistant information for Suregrip & Supagrit infills see pages 76 to 78.