Latham SK, SHD & WAK-Wing Cast-In Place Safety Stair Tread Nosings Data Sheet TYPE-B744VSWAK



longevity is of particular concern. The systems can be installed into the wet concrete topping. All SK,

SHD and WAK-Wing Series Cast-In Place Safety Stair Nosings are suitable for internal or external applications and are available with a wide range of insert colours.

PRODUCT DETAILS - B744VSWAK Latham Asbraloy SK, SHD and WAK-Wing Cast-In Place Safety Stair Nosings are designed for new applications where pedestrian safety and stair

FEATURES

- P5 Slip Classification.
- Super hard wearing.
- Abrasive Silicon Carbide Mineral Insert.
- 16 insert colours available.
- Luminance Reflective Value (LRV).
- UV Stable.

MATERIALS

Standard Supply: Cut to site required lengths, or in full 4600mm lengths.

Brass: Alloy 380 UNS - C38010, Mill Finish. Inserts: Supagrit[™] (Standard - Brown) Silicon Carbide Mineral Inserts.

COMPLIANCE

- Wet Slip Test: Mean British Pendulum (SRV) Classification - P5
- Oil Wet Ramp Test: Slip Resistant Acceptance Group - R12
- Tested to Australian Standard ISO 9239 Reaction to Fire Test for Flooring.

FURTHER TECHNICAL SPECIFICATIONS

- Website Link PDF and DWG Details
- Stair Tread Installation Instructions
- Luminance Contrast Information
- <u>Slip Resistant Testing Information</u>
- <u>Code Compliance Information</u>
- <u>Colour Range Information</u>
- <u>Fire Test Information</u>
- Adhesive Technical Data Sheet
- Full Product Catalogue
- Maintenance Guide
- Photo Gallery
- <u>Accessories Guide</u>
- <u>Warranty</u>



w <u>www.latham-australia.com</u> e sales@latham-australia.com p +612 9879 7888