Latham Asbraloy™ Aluminium ST Surface Mounted Safety Stair Tread Nosing Data Sheet TYPE-FA741ST



PRODUCT DETAILS - FA741ST

Surface mounted stair tread nosings are designed for existing and new applications. The nosing can be installed over the substrate and the tapered profile ensures there is no tripping hazard. The stair tread nosings can be installed on most flooring finishes including stone, concrete, tile, terrazzo, timber, pavers, brick, carpet and vinyl.

FEATURES

- P5 Slip Classification.
- Super hard wearing.
- 50mm Visual Contrast Strip of Full Abrasive Silicon Carbide Mineral Insert.
- 16 insert colours available.
- Luminance Reflective Value (LRV).
- Available factory curved.
- UV Stable.

MATERIALS

Standard Supply: Cut to site required lengths, complete with countersunk holes, stainless steel screws and plastic plugs, or in full 4600mm lengths. Aluminium: 6063-T5, ASTM B221, Mill Finish. Inserts: Suregrip[™] Sparkling Black (standard) Silicon Carbide Mineral Inserts, or Supagrit[™] Coloured Silicon Carbide Mineral Inserts.

COMPLIANCE

- NCC compliant
- AS 1428.1-2021 compliant.
- Wet Slip Test: Mean British Pendulum (SRV)
 Classification P5
- Oil Wet Ramp Test: Slip Resistant Acceptance
 Group R12
- Tested to Australian Standard ISO 9239 Reaction to Fire Test for Flooring.

FURTHER TECHNICAL SPECIFICATIONS

- Website Link PDF and DWG Details
- <u>Stair Tread Installation Instructions</u>
- Luminance Contrast Information
- <u>Slip Resistant Testing Information</u>
- <u>Code Compliance Information</u>
- <u>Colour Range Information</u>
- Fire Test Information
- Adhesive Technical Data Sheet
- Full Product Catalogue
- Maintenance Guide
- Photo Gallery
- <u>Accessories Guide</u>
- Warranty



w <u>www.latham-australia.com</u> e sales@latham-australia.com p +612 9879 7888