



Latham Surface-Line Series Aluminium Expansion Joint Cover

EXA



Illustrated: EXA-25



Aluminium Code ribbed deck	A	B	C	D	Movement	Total Available Movement	Overall Depth	Cover Plate Thickness
EXA-25	25	155	75	49	+25/-15mm	40mm	Surface Mounted	3mm
EXA-50	50	180	100	49	+/-25mm	50mm	Surface Mounted	3mm
EXA-75	75	205	125	49	+/-25mm	50mm	Surface Mounted	4mm
EXA-100	100	230	150	49	+/-25mm	50mm	Surface Mounted	5mm
EXA-125	125	255	175	49	+/-25mm	50mm	Surface Mounted	5mm

FEATURES

- Aluminium floor expansion joint cover.
- Designed to finish flush with the surrounding floor finish (can be suitably packed up to height if required).
- Installed into a minimal recess, or providing the joint width is 62mm or larger, the system can simply hang over the edge of the slabs and no recess is required.

MATERIALS


- Aluminium 6063-T5 mill finish alloy.
- Supplied in 3050mm lengths.
- Spring steel treated centering bar with elongated spherical rods (at ~475mm centres).

FIXINGS

- Side members pre-drilled at ~475mm centres to accept countersunk head 6.5mm fixings.
- We recommend Latham Thixotropic Epoxy Adhesive be used in conjunction for superior securing.

FURTHER TECHNICAL SPECIFICATIONS

- [Website Link - PDF and DWG Details](#)
- [Product Information](#)
- [Joint Specifications](#)
- [Fire Rated Systems](#)
- [Full Product Catalogue](#)
- [Architectural Specifications](#)
- [Warranty](#)



multi directional 6-way movement



indoor use



fire rated (joint widths >50mm)