


# Latham Ultimate Series Aluminium Expansion Joint Cover with Stainless Steel Cover Plate NSS



Illustrated: NSS-20



Stainless Steel Code smooth deck	A	B	C	D	E	F	Movement	Total Available Movement	Overall Depth	Cover Plate Thickness
NSS-20	20	174	75	46	40	77	+45/-10mm	55mm	25mm	3mm
NSS-30	30	184	100	41	35	77	+55/-20mm	75mm	25mm	3mm
NSS-55	55	209	125	41	35	77	+55/-45mm	100mm	25mm	4mm
NSS-80	80	234	150	41	35	77	+55/-65mm	120mm	25mm	4mm
NSS-105	105	259	175	41	35	77	+55/-70mm	125mm	25mm	5mm

## FEATURES

- Aluminium floor expansion joint cover with a stainless steel cover plate.
- Robust system suited to pedestrian applications.
- 25mm depth below floor finish.
- Installed as a retrofit application.

## MATERIALS

- Aluminium 6063-T5 mill finish alloy.
- 304 Grade, 2B finish stainless steel cover plates.
- Supplied in 3050mm lengths.
- Spring steel treated centering bar with nylon spherical balls (at ~475mm centres).

## FIXINGS

- Side member pre-drilled at ~475mm centres to accept countersunk head 8mm fixings.

## FURTHER TECHNICAL SPECIFICATIONS

- [Website Link - PDF and DWG Details](#)
- [Product Information](#)
- [Joint Specifications](#)
- [Fire Rated Systems](#)
- [Full Product Catalogue](#)
- [Architectural Specifications](#)
- [Warranty](#)



multi directional  
6-way movement



indoor & out-  
door use



BFG water  
gutter



fire rated (joint  
widths >50mm)