


25SL - Top View



Aluminium Code	A	в	Movement	Total Available Movement	Overall Depth
Type 25SL	25	47	+/-12mm	24mm	6mm
Type 50SL	50	75	+/-22mm	44mm	6mm
Type 75SL	75	125	+48/-50mm	98mm	6mm
Type 100SL	100	125	+23/-75mm	98mm	6mm



25SL - Bottom View





FEATURES

- Aluminium wall-to-ceiling expansion joint cover.
- Suitable for fixing to masonry, timber, cement sheet, gyprock and other hard surfaced applications.

MATERIALS

- Aluminium 6063-T5 mill finish alloy.
- Supplied in 3050mm lengths.
- Stainless steel spring clips.
- All visual surfaces come with a 20 micron clear anodised finish (contact a Latham representative for alternative anodising or powder coating options).

FIXINGS

The joint clips onto the wall or ceiling with a pre-fixed locking mechanism (hidden from external view) at ~500mm centres.

FURTHER TECHNICAL SPECIFICATIONS

- Website Link PDF and DWG Details
- Product Information
- Joint Specifications
- Fire Rated Systems
- <u>Full Product Catalogue</u>
- Architectural Specifications
- <u>Warranty</u>



w <u>www.latham-australia.com</u> e sales@latham-australia.com p +612 9879 7888



